

# LFP12.8-50





# ITHIUM

SERIES

# **Overview**

NPP Power Lithium-Iron Phosphate batteries offer superb improvement in characteristics compared to lead-acid technology. Due to the extreme cycle and calendar life, LiFePO4 batteries are an excellent long-term investment for your applications. Powerful, lightweight, safe, and smart, the Lithium-Iron Phosphate batteries are the future of the energy storage you can have right now.

#### **Features**

Longer cycle life - Up to 15 times longer cycle life and 5 times longer float/calendar life than lead-acid batteries.

More capacity - Provides up to 100% of usable energy.

Lightweight - 60% lighter than lead-acid batteries.


High discharge rate - Ability to fully discharge the battery at a high rate of discharge.

Fast charging - Charges much faster than conventional sealed lead-acid batteries.

Long cycle life - More than 3000 cycles at 100% depth of discharge.

Intelligent BMS - The battery management system monitors and adapts to battery conditions to maximize performance and safety.

#### **Dimensions & Terminal Type (mm)**



# **Certification & Compliances**















# **Characteristics**

Electrical		
Nominal voltage		12.8V
		50Ah
Nominal capacity at 5 hours rate (25°C)  Energy		640Wh
Charge Efficiency at 0.2C (25°C)		99.5%
Discharge Efficiency at 1C (25°C)		96-99%
Approx. internal resistance (25°C)		≤16.0 mΩ
Cycle life / 0.2C 100% D.O.D		
Capacity affected by temperature	40°C	>2000 cycles
	25°C	101%
	0°C	100%
	0 0	90%
	-10°C	75%
Mechanical	1	
Dimensions	Length	197±2mm (7.76inch)
	Width	165±2mm (6.50inch)
	Height	170±2mm (6.69inch)
	Total height	170±2mm (6.69inch)
Terminal type		T14
Torque		5.1±0.6N.m
Weight		7.60kg (16.75lbs)±4%
Water & Dust resistance		IP65
Battery container ABS UL94-HB		V-0 optional
Cell strings		4 strings
Temperature		
Nominal operatir	ng temperature	25°C±3 (77±5°F)
Operating temperature range	Discharge	-20°C~60°C (-4°F~140°F)
	Charge	0°C~45°C (32°F~113°F)
	Storage	0°C~40°C (32°F~104°F)
Charging		
Charging voltage at 25°C		14.6V
Standard charge mode (25°C±2°C, <75%RH)		0.2CA Constant Current to 14.6V, then Constant Volt- age 14.6V until the curren drops to 0.02CA. Rest 30 minutes, before use.
Nominal charging current		10A
Maximum charging current		25A
Charging cut-off voltage		14.6V
Discharging		
Continuous discharge current		50A
Maximum pulse discharge current (<100ms)		150A
Discharge cut-off voltage		11.2V
Self discharge rat	e (25°C)	≤3%/month
Comunication	& connection	
	protocol (optional)	N/A
Communication	protocor (optional)	14/73
SOC (optional)	protocor (optional)	LED/Bluetooth

4 in string, 6 in parallel Compliant to: IEC 62133-2

The data in this document is subject to change without notice and become contractual only after written confirmation. Please contact NPP Power for the latest available version.

#### **Guangdong NPP New Energy Co., Ltd.**

No.3 Hongli Road, Miaobian Community, Liaobu Town, Dongguan, Guangdong Province, China.

#### Guangzhou NPP Power Co., Ltd.


No.67 Lianglong Road, Huashan Town, Huadu District, Guangzhou,

Email: info@nppower.com.cn Tel: +86 20 37887 390




# SERIES


# Discharge characteristics (25°C)




# Temperature effects on discharge (0.5C)




# Charging Time on S.O.C. (25°C)



# Charge characteristics (25°C)



# Cycle life on D.O.D. (25°C)



D.O.D. - depth of discharge S.O.C. - state of charge

# Self discharge characteristics

